

RANGE SET-UP: SHOOTERS BOXES ARE 3'X3'. PLATE MACHINE(PM) IS 40 YDS DOWN RANGE FOR BOX A, T1-T3 SET IN FRONT OF THE PM, T4-T6 ARE SET FACING ACROSS RANGE, T7-T15 ARE SET GROUPS OF THREE, EQUALLY SPACED ACROSS REMAINER OF THE RANGE AND T16-T18 ARE OPPOSITE T1-T3.

STAGE PROCEDURE

SHOOTER STARTES IN BOX A , ON SIGNAL ENGAGE PM , T1-T3 AND T16-18 ONLY , MOVE TO BOX B AND ENGAGE T13-T15 AND T4-T6 ONLY, MOVE TO BOX C AND ENGAGE T10-12 ONLY, MOVE TO BOX D AND ENGAGE T7-T9 ONLY. ENGAGE EACH PAPER TARGET WITH TWO ROUND.

SCORING: COMSTOCK

TARGETS: 18 PAPER & 6 STEEL PLATES SCORED ROUNDS: 42

MIN:DISTANCE: 10 YDS MAX DISTANCE: 40YDS START SIGNAL: AUDIBLE STOP SIGNAL: AUDIBLE

START POSITION: STANDING WITH HANDS RELAXED AT SIDE, FACING DOWN RANGE PENALTIES: PREMATURE START +5 SEC EACH MISS +5 SEC EACH FOOT FAULT +5 SEC